



G-T[®] RING

Sealing Solutions for Demanding Environments

HIGH-PRESSURE, HIGH-TEMPERATURE SEALS

The unique G-T[®] Ring provides a compact, double-acting seal for use in new designs or existing applications where O-rings are failing. The G-T Ring can be retrofitted into standard grooves designed for O-rings with one, two or no backups. This proven seal combines a tough, resilient, T-shaped ring with precisely dimensioned, pressure-actuated, anti-extrusion rings for use with pressure ratings up to 43,500 psi (3000 bar). For higher pressures consult Greene, Tweed.



FEATURES

- Easy installation
- Excellent resistance to extrusion
- Extended service life
- Unique configuration eliminates seal roll and spiral failure
- Low pressure sealing

The G-T Ring is a static or dynamic seal in “rod” or “piston” configurations for demanding oilfield applications, e.g., cylinders, jacks, intensifiers, tensioners, BOPs, logging equipment, jars, shock subs, bumper subs, pumps, valves and well head equipment.

Contact Us

Greene, Tweed
Oilfield
Houston, TX, USA

Tel: +1.281.765.4500
Tel: +1.800.927.3301
Fax: +1.281.765.4553

www.gtweed.com

Statements and recommendations in this publication are based on our experience and knowledge of typical applications of this product and shall not constitute a guarantee of performance nor a modification or alteration of our standard warranty that shall be applicable to such products.